







仅供参考

REV.	REVISION RECORD	DATE
A0	新图面发行	2017.06.16

Specification:  
 Current Rating : 3.0AMP  
 Temperature Range : -40°Cto+105°C  
 Contact Resistance : 20mΩ Max  
 Insulation Resistance : 1000MΩ Min  
 Withstanding Voltage : AC 500V  
 Material:  
 Insulator : Polyester (UL94V-0)  
 Standard:PBT/PA6T/LCP  
 Contact: Brass  
 Plating : Au or Sn Over 50u" Ni



Pin数	尺寸A	尺寸B
2×1	-	2.50
2×2	2.50	5.00
2×3	5.00	7.50
2×4	7.50	10.00
2×5	10.00	12.50
2×6	12.50	15.00
2×7	15.00	17.50
2×8	17.50	20.00
2×9	20.00	22.50
2×10	22.50	25.00
2×11	25.00	27.50
2×12	27.50	30.00
2×13	30.00	32.50
2×14	32.50	35.00
2×15	35.00	37.50
2×16	37.50	40.00
2×17	40.00	42.50
2×18	42.50	45.00
2×19	45.00	47.50
2×20	47.50	50.00
2×21	50.00	52.50
2×22	52.50	55.00
2×23	55.00	57.50
2×24	57.50	60.00
2×25	60.00	62.50
2×26	62.50	65.00
2×27	65.00	67.50
2×28	67.50	70.00
2×29	70.00	72.50
2×30	72.50	75.00
2×31	75.00	77.50
2×32	77.50	80.00
2×33	80.00	82.50
2×34	82.50	85.00
2×35	85.00	87.50
2×36	87.50	90.00
2×37	90.00	92.50
2×38	92.50	95.00
2×39	95.00	97.50
2×40	97.50	100.00



Height
H=1.5mm, 3.0mm, 3.3mm

	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	深圳市思拓展电子有限公司 SHENZHEN SINOTOP ELECTRONICS CO.,LTD 公司网址: www.szsituo.cn      公司电话: 0755-23765350 邮 箱: 2850175982@qq.com      公司传真: 0755-23765341	PART. NO: ST-PH-250-0086
	LINEAR	ANGLES					APPROVED
UNIT: MM	0.0±0.30	X° REF±6°	DESIGNER	TITLE: Pitch2.50mm Pin Header, Single Plastic, Dual Row, Horizontal SMT Type	REV: A0	SHEET: 1/1	
SIZE: A4	0.000±0.10	X° X'±2°	DRAWN 肖坤权	2017.06.16			