





仅供参考

REV.	REVISION RECORD	DATE
A0	新图面发行	2017.06.16

Specifications:
 Voltage Rating : 250V AC/DC
 Current Rating : 3A AC,DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -55°C~+150°C



Unit: mm



Recommended PCB Layout

Part No.	Dimensions		
	A	B	C
2*2P	2.0	2.74	9.24
2*3P	4.0	4.74	11.24
2*4P	6.0	6.74	13.24
2*5P	8.0	8.74	15.24
2*6P	10.0	10.74	17.24
2*7P	12.0	12.74	19.24
2*8P	14.0	14.74	21.24
2*9P	16.0	16.74	23.24
2*10P	18.0	18.74	25.24
2*11P	20.0	20.74	27.24
2*12P	22.0	22.74	29.24
2*13P	24.0	24.74	31.24
2*14P	28.0	28.74	33.24
2*15P	30.0	30.74	35.24
2*16P	32.0	32.74	37.24
2*17P	34.0	34.74	39.24
2*18P	36.0	36.74	41.24
2*19P	38.0	38.74	43.24
2*20P	40.0	40.74	45.24

Material	Color	PIN Material
LCP,UL94V-0	Black	Brass

	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	深圳市思拓展电子有限公司 SHENZHEN SINOTOP ELECTRONICS CO.,LTD 公司地址: www.szstuo.cn 公司电话: 0755-23765350 邮箱: 2850175982@qq.com 公司传真: 0755-23765341	PART NO: STP42017W00-2xNPA-A3-RS
	LINEAR	ANGLES					
UNIT: MM	0.00±0.25	X° REF±6°	DESIGNER			TITLE:	DWG. NO:
SIZE: A4	0.000±0.15	X° X'±2°	DRAWN	肖坤权	2017.06.16	2.00mm pitch Single Wafer	REV: A0 SHEET: 1/1