



仅供参考

REV.	REVISION RECORD	DATE
A0	新图面发行	2017.06.16

Specifications:
 Contact resistance: $\leq 20m\Omega$
 Insulation resistance: $\geq 1000M\Omega$
 Rated voltage: 125V AC DC
 Rated current: 3.0A AC DC
 Withstand Voltage: 1000V AC/minute
 Temperature Range: $-40^{\circ}C \sim +105^{\circ}C$
 Housing: NYLON66 UL94V-0 NATURAL



PIN	Dimensions	
	A	B
10P	8.00	12.00
12P	10.00	14.00
14P	12.00	16.00
16P	14.00	18.00
20P	18.00	22.00
22P	20.00	24.00
24P	22.00	26.00
40P	38.00	42.00

	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	深圳市思拓展电子有限公司 SHENZHEN SINOTOP ELECTRONICS CO., LTD 公司网址: www.szstuo.cn 公司电话: 0755-23765350 电子邮箱: 2850175982@qq.com 公司传真: 0755-23765341	PART. NO: ST-WF-200-010Y	
	LINEAR	ANGLES					APPROVED	DWG. NO:
	0.0 ± 0.30	X° REF ± 6°	DESIGNER					
	UNIT: MM	0.00 ± 0.20	X° ± 3°	TITLE: 2.00mm PITCH HOUSING				
SIZE: A4	0.000 ± 0.10	X° X' ± 2°	DRAWN	肖坤权	2017.06.16	REV: A0	SHEET: 1/1	